



Power PLUS

Trusted. Precision
Relative Power \uparrow 100

Built using advanced technology, Fenner Power PLUS transmission belts achieve economic performance by use of low elongation polyester cords and abrasion resistant impregnated jacket fabric. It conforms to DIN 7753(German Institute for Standard-

Benefits

- > Heat and Oil Resistant
- > Accuracy and stability of length
- > Ideal for use in single or multi-belt drives
- > One-shot tensioning for fit-and-forget reliability
- > Extended temperature range -40°C to +70°C
- > PB® (Precision Built) eliminating the need for matching
- > Fully approved by the following International Standards:
 - * ISO 4184 (International Standards Organisation)
 - * BS 3790 (British Standard)
 - * Static conductive in accordance with ISO 1813
 - * Conforms to American Petroleum Institute specifications



Power PLUS Belt Sections and Size Range

Profile	SPZ/3V	SPA	SPB/5V	SPC	8V / DELTA
Metric Length Range (mm)	487 - 3550	732 - 4500	1250 - 8000	2000 - 12500	2540 - 11430



Reliable | Trusted | Connected



FPT Far East Pte. Ltd

29 Changi South Avenue 2 #04-00, ABV Building, Singapore 486444

(65) 6545 6630 (65) 6545 7730 / 7720 sales@fpt.com.sg www.fpt.com.sg

